

Technical Specification

SM-TL-L

Product Name:	SM-TL-L Range
Category:	Surface Mount Track Light with Lens
Description:	Adjustable surface mount spot with lens



Fitting Material	High pressure die-cast aluminium housing
Trim adjustability	Fixed Trim, Deep Recessed
Available finishes	BK (Black)
Optic Type	Lens
IP Rating	IP65
Mounting Type	Screw-in mounting bracket
LED Colours (CCT)	3000K / 4000K
LED Colour Consistency	<3 SDCM
Colour Rendering Index (CRI)	CRI90 (CRI95+ on request)
LED Lifetime	L80B10 >50,000 hrs at Ta = 25° Celsius
Control Options	Non-dim (N)
Operating Voltage/ Frequency	220 – 240 V/ 50 – 60 Hz
Warranty	5-year warranty as per LEDwise standard terms of the warranty
Manufacture	Designed and manufactured in South Africa



Technical Specification

SM-TL-L

Product Code	Plug Power (W)	Luminaire Output (lm)		Beam Angle (°)	Fitting Colour
		3080 (3000K)	4080 (4000K)		
SM-TL10-L	9.53	1179	1237	24°, 50°	BK
SM-TL15-L	13.94	1556	1647	24°, 50°	BK
SM-TL20-L	19.94	2191	2346	24°, 50°	BK

*Values accurate to within 10%

Dimensions			
Product Code	Diameter (mm)	Height (mm)	Cut-out
TL10-L	95	152	N/a
TL15-L	95	152	N/a
TL20-L	95	152	N/a

Product Ordering Code				
Example: SM-TL10-L – 4080 - 24° - BK - N				
SM-TL10-L	4080 = 4000K CRI80	24°	BK	N (Non-Dim)
Product Code	LED Colour CRI	Beam Angle	Fitting Colour	Control

Document Info
SM-TL-L Rev 2

